



Non-ASME Expansion Tanks

Series "PT" pre-charged tanks

- Residential and commercial applications
- Controls system pressure
- Protects plumbing fixtures
- Eliminates relief valve blow-off
- FDA approved materials
- High maximum operating temperatures
- High working pressures of 150 PSI (1035kPa)



Designed for potable
hot water systems



Series "PT" potable hot water tanks

Description

The Series PT expansion tank is designed to absorb the forces of expanding water and protect a potable water system from pressure build up. The FDA approved heavy duty butyl diaphragm with polypropylene liner (sizes PT-5 through PT-210V) and FDA approved heavy duty butyl bladder (sizes PT-451 through PT-457) completely isolate the water from the steel shell.

Models PT-5 through PT-210V are listed by NSF 61.

Residential/light commercial non-ASME diaphragm tanks

Maximum working pressure:

- PT-5 & PT-12150 PSI (1035kPa)
- PT-25V thru PT-210V 100 PSI (689kPa)
- Maximum operating temperature 200°F m(93°C)
- Materials: steel shell, polypropylene liner, butyl diaphragm
- System connection: PT-25V thru PT-210V are stainless steel. All others are brass.
- Factory pre-charge38 PSI (276kPa)

Commercial non-ASME bladder tanks

- Maximum working pressure150 PSI (1035kPa)
- Maximum operating temperature 240°F m (116°C)
- Materials: steel shell, butyl bladder
- System connectionBronze
- Factory pre-charge55 PSI (379kPa)

Dimensions: gallons (lts), inches (mm), weights: lbs. (kg)


Residential/light commercial non-ASME diaphragm tanks

Model number	Part number	Volume gallons (liters)		Height A	Diameter B	System connection	Approx. shpg. wt. lbs. (kg)
		Tank	Acceptance				
PT-5	1BN317LF	2 (7.5)	0.9 (3.4)	12 ⁵ / ₈ (321)	8 (203)	³ / ₄ " (19) NPTM	5 (2.3)
PT-12	1BN318LF	4.4 (16.6)	3.2 (12)	15 (381)	11 (279)		9 (4.1)
PT-25V	1BN319LF	10.3 (39)	10.3 (39)	19 ¹ / ₂ (489)	15 ³ / ₈ (391)	³ / ₄ " (19) NPTM	23 (10.4)
PT-30V	1BN320LF	14 (53)	11.3 (43)	24 ³ / ₄ (629)	15 ³ / ₈ (391)	1" (25) NPTF	24 (11)
PT-42V	1BN321LF	20 (76)	11.4 (43)	32 ¹ / ₂ (825)	15 ³ / ₈ (391)		34 (15.5)
PT-60V	1BN322LF	34 (129)	34 (129)	31 ³ / ₄ (808)	22 (559)	1 ¹ / ₄ " (32) NPTF	56 (25.5)
PT-80V	1BN323LF	44 (167)	33.8 (128)	36 ¹ / ₂ (927)	22 (559)		64 (29.1)
PT-180V	1BN324LF	62 (235)	34.1 (129)	48 ¹ / ₂ (1232)	22 (559)		89 (40.5)
PT-210V	1BN325LF	86 (326)	46.4 (176)	46 (1168)	26 (660)		116 (52.8)


Commercial non-ASME bladder tanks

Model number	Part number	Volume gallons (liters)		Height A	Diameter B	System connection	Approx. shpg. wt. lbs. (kg)
		Tank	Acceptance				
PT-451	1BN010LF	158 (600)	102.7 (388)	73 ¹ / ₄ (1861)	30 (762)	2" (50) NPTF	508 (230)
PT-452	1BN011LF	211 (800)	137.2 (519)	91 (2317)	30 (762)		760 (345)
PT-453	1BN012LF	264 (1000)	171.6 (650)	85 ⁵ / ₈ (2175)	36 (914)	3" (76) NPTF	810 (368)
PT-454	1BN013LF	317 (1200)	206.1 (780)	98 (2489)	36 (914)		914 (415)
PT-455	1BN014LF	370 (1400)	240.5 (910)	110 ³ / ₈ (2804)	36 (914)		1018 (462)
PT-456	1BN015LF	422 (1600)	274.3 (1038)	81 ⁷ / ₈ (2080)	48 (1219)		1655 (750)
PT-457	1BN016LF	528 (2000)	343.2 (1300)	97 ¹ / ₄ (2470)	48 (1219)		1925 (873)


Dimensions subject to change. Not to be used for construction purposes.



PT-5 through PT-12



PT-25V through PT-210V



PT-451 through PT-457

Xylem Inc.
8200 N. Austin Avenue
Morton Grove, Illinois 60053

Phone: (847) 966-3700
Fax: (847) 965-8379
www.xylem.com/bellgossett

Subject to change without notice. All information presented herein is believed reliable and in accordance with accepted engineering practices. Xylem makes no warranties as to the completeness of this information. Users are responsible for evaluating individual product suitability for specific applications. Xylem assumes no liability whatsoever for any special, indirect or consequential damages arising from the sale, resale or misuse of its products.

©2025 Xylem and Bell & Gossett are trademarks of Xylem, Inc. or one of its subsidiaries. All other trademarks are the property of their respective owners.

A-353E 4/2025

xylem
Let's Solve Water